



EstateTM

Ornamental Entry Gates



Heavy-Duty Welded Aluminum
Maintenance-Free Polyester Finish

DOUBLE SWING

Estate™ Gates are not only beautiful but they are strong and maintenance-free. All framework is 1/4" thick and all intersections are welded.



A statement in itself. Adding value and aesthetics to complete the look of elegance.

Make an impression with this Majestic Estate™ Entry Gate.





Classic Estate™

WALK



Genesis Estate™



Majestic Estate™

Private residences, large estates and condominium complexes are selecting the elegant appeal of the Estate™ Walk Gate.


CANTILEVER




Genesis Estate Cantilever Gate with Finials

The Estate™ design on the TransPort™ top track combines the look of elegance with the functionality and space efficiency of the sliding enclosed-track system.


STYLES




CLASSIC




MAJESTIC




GENESIS



BLACK



BRONZE



SAND



WHITE

For actual color, call for color samples

COLORS

ACCESSORIES



Triad



Butterfly



Rings



Quad Flare




Florentine



Letters




Barrel Hinges



Bolt-On Hinges




Bolt-On Fork Latch



For Single Gates Only

Ameristar Lock



Cane Bolt

HARDWARE

SPECIFICATION

Ornamental Aluminum Entry Gates

2.01 MANUFACTURER

The gate system conform to Ameristar Estate™ entry gate (specify Lancelot or Guinevere) design series, (specify single or double), with (specify total opening in feet) opening, (specify height in feet at post) to (specify height in feet at center of opening), tall (specify cross-sectional size and gauge of posts) posts.

2.02 MATERIALS

- A. The materials used for entry gate framing shall be manufactured from aluminum (Designation 6063-T-6) with a yield strength of 25,000 psi, a tensile strength of 30,000 psi and a standard mill finish.

- B. Rails and Gate Ends shall have a minimum wall thickness of 1/4". Rails shall be 1" x 2" channel. Ends shall be 2" square. Pickets are 3/4" square by 1/8" wall thickness.

2.03 FABRICATION

- A. Components shall be precut to specified lengths.
 B. All intersections shall be welded construction.
 C. Completed gate leaves shall be thoroughly inspected at the factory prior to shipping.

WARRANTY

Ameristar Fence Products hereby certifies that its gates are free from defects in material or workmanship. (Note: Accidental damages, defects resulting from improper installation techniques and damage from abuse or vandalism are not included herein).

Distributed by:

Rev. 11/08