

VIKING ACCESS SYSTEMS™

HIGH TRAFFIC COMMERCIAL GATE SOLUTION




H-10

RESIDENTIAL AND COMMERCIAL

SLIDE GATE OPERATOR


CLASS I, CLASS II, CLASS III, AND CLASS IV VEHICULAR GATE OPERATOR

 VIKING BLUE ENABLED


 SOLAR EFFICIENT OPERATION

H-10™ PRODUCT INFORMATION AND SPECIFICATIONS

The H-10™ gate operator has the capacity to operate slide gates up to 2000 lbs. and 45 feet in length at 100% duty cycle under extreme conditions. Its efficient mechanism provides a solution for high traffic commercial slide gate applications. The Viking H-10™ gate operator offers efficiency and technology combined in a single package. This operator is UL Listed 18TC UL325 and UL991.



On-board lightning protection



Innovative fine tune adjustment for the end of gate travel (down to 1/8")



Soft-Stop / Soft-Start with intelligent Obstruction Detection





Loop rack included



Back-drivable unit features direct drive mechanism

120 / 220 VAC single phase power source

Fail-safe / Fail-secure



Operational Voltage	... 24 VDC with 1 H.P. Motor
Main Power Source	... 120 / 220 VAC Single Phase
Battery	... 7 AmpHr 12 VDC x 2
Max Gate Capacity	... 2000 lbs. / 45 feet
Max Operating Speed	... 12" per second
Battery Backup Operation	... 100 Full Cycles (1000 lbs. / 20' gate)
Max Duty Cycle	... 100% Continuous Cycle
Operating Temperature	... - 4° F to + 158° F



7 YEAR RESIDENTIAL / 5 YEAR COMMERCIAL WARRANTY