

VIKING ACCESS SYSTEMS™

TRANSPARENT SWING GATE AUTOMATION




i-8

RESIDENTIAL AND COMMERCIAL

UNDERGROUND OPERATOR

CLASS I, CLASS II, CLASS III, AND CLASS IV VEHICULAR GATE OPERATOR




i-8™ PRODUCT INFORMATION AND SPECIFICATIONS

The answer for an elegant access control is fulfilled with the i-8 gate operator. The discreteness of the installation, the flexibility of operation, the efficiency of automation, and the adaptability of integration makes the i-8 gate operator a perfect solution in situations where aesthetics are required to satisfy the most exquisite taste. This operator is UL Listed 18TC UL325 and UL991.

Key for manual release



Single stage efficient gearing system




Configurable to open left or open right

Built-in adjustable positive stop


Water resistant gear head unit

Stainless steel casing available

Powerful and efficient water resistant DC motor in direct drive configuration



 VIKING BLUE ENABLED

 SOLAR EFFICIENT OPERATION

Operational Voltage	... 24 VDC with 1/2 H.P. Motor
Main Power Source	... 120 / 220 VAC Single Phase
Battery	... 7 AmpHr 12 VDC x 2
Max Gate Capacity	... 650 lbs. / 12 feet
Max Operating Speed	... 10-13 seconds per 90°
Battery Backup Operation	... 400 Full Cycles (600 lbs. / 12' gate)
Max Duty Cycle	... 100% Continuous Cycle
Operating Temperature	... - 4° F to + 158° F



3 YEAR RESIDENTIAL / 2 YEAR COMMERCIAL WARRANTY