

VIKING ACCESS SYSTEMS™

EFFICIENT TECHNOLOGY IN SLIDE GATE OPERATION




13

RESIDENTIAL AND COMMERCIAL

SLIDE GATE OPERATOR


CLASS I, CLASS II, CLASS III, AND CLASS IV VEHICULAR GATE OPERATOR

 **VIKING BLUE ENABLED**


 **SOLAR EFFICIENT OPERATION**

L-3™ PRODUCT INFORMATION AND SPECIFICATIONS


The L-3™ gate operator has the capacity to operate slide gates up to 1200 lbs. and 40 feet in length at 100% duty cycle under extreme conditions. Its efficient mechanism provides a solution for high traffic commercial slide gate applications. The Viking L-3™ gate operator offers efficiency and technology combined in a single package. This operator is UL Listed 18TC UL325 and UL991.



On-board lightning protection



Innovative fine tune adjustment for the end of gate travel (down to 1/8")



Soft-Stop / Soft-Start with intelligent Obstruction Detection





Loop rack included



Built in optional auto-open feature in case of power failure

Back-drivable unit features direct drive mechanism

120 / 220 VAC single phase power source



| | |
|--------------------------|--|
| Operational Voltage | ... 24 VDC with 1/2 H.P. Motor |
| Main Power Source | ... 120 / 220 VAC Single Phase |
| Battery | ... 7 AmpHr 12 VDC x 2 |
| Max Gate Capacity | ... 1200 lbs. / 40 feet |
| Max Operating Speed | ... 12" per second |
| Battery Backup Operation | ... 100 Full Cycles (1000 lbs. / 20' gate) |
| Max Duty Cycle | ... 100% Continuous Cycle |
| Operating Temperature | ... - 4° F to + 158° F |



7 YEAR RESIDENTIAL / 5 YEAR COMMERCIAL WARRANTY